


Z-Foil Ultra High-Precision SMT Resistor (Molded, J-Lead Terminal)



FEATURES

- Temperature coefficient of resistance (TCR): 0.05 ppm/°C typical (0°C to +60°C) by New Generation Z-Foil Technology
- 0.2 ppm/°C typical (-25°C to +125°C, +25°C ref.)
- Resistance tolerance: to ±0.01%
- Power coefficient “ΔR due to self heating”: 5 ppm at rated power (typical)
- Power rating: to 200 mW (MPP) and 250 mW (MQP) at +70°C
- Load life stability: to ±0.005% at 70°C, 2000h at rated power (typical)
- Not restricted to standard values, we can supply specific “as required” values at no extra cost or delivery (e.g., 1K2345 vs. 1K)

COMPOSITION OF TYPE NUMBER

Example:

MPP 10K005* T L

Tape & Reel Package Required
Resistance Tolerance
Resistance Value
Type


Resistance value, in ohm, is expressed by a series of six characters, five of which represent significant digits. R or K is a dual-purpose letter that designates both the value range (R for ohmic; K for kilo-ohm) and the location of the decimal point.

* Imprinting indicates up to 3 significant digits but ordered resistance value is traceable by date code

TCR, RESISTANCE RANGE, TOLERANCE, RATED POWER


Type	TCR (ppm/°C) -25°C to +125°C	Resistance Range (Ω)	Resistance Tolerance (%)	Rated Power (W) at 125°C
MPP	±0.2±3.8	30 to <50	±0.1(B)	0.1
	±0.2±2.8	50 to <100	±0.1(B)	
	±0.2±1.8	100 to <1k	±0.02(Q) ±0.05(A) ±0.1(B)	
		1k to ≤20k	±0.01(T) ±0.02(Q) ±0.05(A) ±0.1(B)	
MQP	±0.2±3.8	30 to <50	±0.1(B)	0.125
	±0.2±2.8	50 to <100	±0.1(B)	
	±0.2±1.8	100 to <1k	±0.02(Q) ±0.05(A) ±0.1(B)	
		1k to ≤40k	±0.01(T) ±0.02(Q) ±0.05(A) ±0.1(B)	

CONFIGURATION (DIMENSIONS IN mm)




Type	MPP	MQP
L	3.2±0.2	4.5±0.2
W	2.5±0.2	3.2±0.2
H	2.0±0.2	
L1	0.6±0.2	0.8±0.2
W1	1.4±0.3	
W2	2.3±0.2	3.0±0.2
H1	1.5±0.3	
t	0.15±0.05	

POWER DERATING CURVE



FREQUENCY CHARACTERISTICS



PERFORMANCE				
Parameters	Test Condition	Specification		Typical MPP/MQP
		MP/MQ	MPP/MQP	
Maximum Rated Operating Temperature Working Temperature Range Maximum Working Voltage Maximum Working Current			125°C -65°C to +175°C MPP = 50V, MQP = 100V 350 mA	
Thermal Shock Overload	-65°C/30 min. ↔ +150°C/30 min., 5 cycles Rated Voltage x 2.5, 5 sec.	±0.05%	±0.01%	±0.005%
Low Temperature Storage and Life Outstanding PC Board Bending	-65°C, No Load, 24 hrs. → Rated Voltage, 45 min. 3 mm Bend, 60 sec.	±0.05%	±0.01%	±0.005%
Dielectric Withstanding Voltage Insulation Resistance Resistance to Soldering Heat Moisture Resistance	AC 200V, 1 min. DC 100V, 1 min. 260°C, 10 sec. +65°C to -10°C, 90% RH to 98% RH, Rated Voltage, 10 cycles (240 hrs.)	±0.01%	±0.01%	±0.005%
Shock Vibration, High Frequency	100G, 6 ms, Sawtooth Wave, X, Y, Z, each 10 shocks 20G, 10 Hz to 2,000 Hz to 10 Hz, 20 min., X, Y, Z, each 2.5 hrs.	±0.02%	±0.02%	±0.01%
Storage Life	15°C to 35°C, 15% RH to 75% RH, No Load, 10,000 hrs.	±0.005%	±0.005%	±0.0025%
High Temperature Exposure	175°C, No Load, 2,000 hrs.	±0.05%	±0.05%	±0.03%
Life	70°C, Rated Power, 1.5 hr. – on, 0.5 hr. – off, 2,000 hrs. 70°C, Rated Power x 2, 1.5 hr. – on, 0.5 hr. – off, 2,000 hrs.	—	±0.01%	±0.005%
		—	±0.03%	±0.01%

TAPE AND REEL PACKAGE (BASED ON EIA-481-1) (DIMENSIONS IN mm)																		
Tape Dimensions										Reel Dimensions								
Type	A	B	C	D	E	F	G	H	J	A	N	B	C	D	W1	W2	r	
MPP	2.8 ±0.2	3.9 ±0.2	12.0 ±0.3	5.5 ±0.05	1.75 ±0.1	4.0 ±0.1	2.0 ±0.05	4.0 ±0.1	Dia. 1.5 ±0.1-0	Dia. 178 ±2	Dia. 60 min.	Dia. 13 ±0.5	Dia. 21 ±0.8	2 ±0.5	12.4 +2.0-0	18.4 max.	1.0 ±0.5	
MQP	3.6 ±0.2	5.2 ±0.2	12.0 ±0.3	5.5 ±0.05	1.75 ±0.1	8.0 ±0.1	2.0 ±0.05	4.0 ±0.1	Dia. 1.5 ±0.1-0	Reel Capacity		MPP: 1,200 pieces/reel MQP: 800 pieces/reel						

PRECAUTION IN USING FACE-BONDED CHIP RESISTORS

- Storage**
Storage conditions or environment may adversely affect solderability of the exterior terminals. Do not store in high temperature and humidity. The recommended storage environment is lower than 40°C, has less than 70% RH humidity and is free from harmful gases such as sulphur and chlorine.
- Caution in Soldering**
 - Hand Soldering**—Hand soldering is applicable as shown at right. Recommended
 - Temp. of iron tip: 240°C to 270°C
 - Power of iron: 20W or less
 - Diameter of tip: dia. 3 mm max.
 - Solder Reflow in Furnace**
Recommended
 - Peak temperature: 250+0/-5°C
 - Holding time: 10 sec. max.
 - To cool gradually at room temperature
 - Dipping in Solder (Wave or Still)**
Recommended
 - Temp. of solder: 260°C max
 - Length of dipping: 10 seconds
 - To cool gradually at room temperature
 - Other**
Corrosion-free flux, such as rosin, is recommended. Do not apply pressure to the molded housing immediately after soldering.
- Cleaning**
Use volatile cleaner such as methylalcohol or propyl alcohol.
- Circuit Board Design**
The dimensions of solder land must be determined in conformity with the size of resistors and with the soldering method. They are also subject to the mounting machine and the material of the substrate. See example below.

Type	A	B	C	D
MPP	1.6 to 2.0	0.5 to 1.5	2.2 to 2.6	1.8
MQP				2.5

When parts are mounted on a board in high density, solder can possibly attach to the resistors in an excessive amount to affect performance or reliability of the resistors. To prevent this effect, the use of solder resist is recommended to isolate solder lands.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.